

SmartZone™ G5 ベーシック PDU & インテリジェント PDU

ベーシックシリーズ

地域	フォームファクタ	入力プラグタイプ	入力電圧範囲	入力電流 (相ごと)	サーキットブレーカー	皮相電力 (kVA)	アウトレット数	アウトレットタイプ	出力電圧	バンドウイット部品番号		
200		NEMA L5-20P	100-120VAC	20	0	1.9 kVA	12	(12)5-20R	100	P12BF6M-BL6C		
	☒	8	NEMA L6-20P	200-240VAC	20	0	3.3 kVA	12	(12)C13	200	P12BF7M-BL6C	
	☒	8	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	12	(12)C13	200	P12BF8M-BL6C	
	☒	8☒	NEMA L5-20P	100-120VAC	20	0	1.9 kVA	16	(16)5-20R	100	P16BF9M-BL1C	
	☒	8	NEMA L5-30P	100-120VAC	30	2	2.9 kVA	16	(16)5-20R	100	P16BG0M-BL6C	
	☒	8☒	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	20	(20)C13	200	P20BG2M-BL1C	
	☒	8☒	NEMA L5-20P	100-120VAC	20	0	1.9 kVA	22	(20)C13, (2)C19	100	P22BG3M-BL1C	
	☒	8☒	NEMA L5-30P	100-120VAC	30	2	2.9 kVA	22	(22)5-20R	100	P22BG4M-BL1C	
	☒	8☒	NEMA L6-20P	200-240VAC	20	0	3.3 kVA	22	(20)C13, (2)C19	200	P22BG5M-BL1C	
	☒	8☒	NEMA L5-30P	100-120VAC	30	2	2.9 kVA	22	(22)5-20R	100	P22BH9M-BL1R	
	☒	8☒	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	24	(20)C13, (4)C19	200	P24BG7M-BL1C	
	☒	8☒	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	42	(36)C13, (6)C19	200	P42BH0M-BL1C	
300		NEMA L6-30P	200-240VAC	30	2	5.0 kVA	42	(36)C13, (6)C19	200	P42BJ0M-BL1R		
	☒	8	IEC 60309 3P+E 9h 60A (IP44)	200-240VAC	60	6	17.3 kVA	6	(6)C19	200	P06B03M	
	☒	8☒	IEC 60309 3P+E 9h 60A (IP44)	200-240VAC	60	6	17.3 kVA	24	(12)C13, (12)C19	200	P24B14M	
	☒	8	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	6	(6)C19	200	P06BF5M-BL6C	
	☒	8☒	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	18	(18)C13	200	P18BG1M-BL1C	
	☒	8☒	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	36	(30)C13, (6)C19	200	P36BG8M-BL1C	
	☒	8☒	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	42	(36)C13, (6)C19	200	P42BH1M-BL1C	
	200	☒	8	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	6	(6)C19	240	P06B37M
		☒	8	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	6	(6)C19	240	P06B38M
		☒	8☒	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	24	(12)C13, (12)C19	240	P24B12M
		☒	8☒	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	30	(24)C13, (6)C19	240	P30B13M
		☒	8☒	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	42	(30)C13, (12)C19	240	P42B11M
☒		8☒	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	42	(36)C13, (6)C19	240	P42B44M	
☒		8	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	6	(6)C19	240	P06B04M	
☒		8☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(12)C13, (12)C19	240	P24B02M	
☒		8☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(24)C13, (12)C19	240	P36B02M	
☒		8☒ ☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(48)C13	240	P48B03M	
☒		8☒ ☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	54	(48)C13, (6)C19	240	P54B03M	

☒ : : 30 () : 45 : /

MI (Monitored Input) シリーズ

地域	フォームファクタ	入力プラグタイプ	入力電圧範囲	入力電流 (相ごと)	サーキットブレーカー	皮相電力 (kVA)	アウトレット数	アウトレットタイプ	出力電圧	バンドウイット部品番号	
100-240VAC		1	NEMA L5-20P	100-120VAC	20	0	1.9 kVA	8	(8)5-20R	100	P08DE8M-BL6C
	☒	8	NEMA L6-20P	200-240VAC	20	0	3.3 kVA	12	(12)C13	200	P12DE9M-BL6C
	☒	8	NEMA L5-30P	100-120VAC	30	2	2.9 kVA	16	(16)5-20R	100	P16DF0M-BL6C
	☒	8	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	16	(12)C13, (4)C19	200	P16DF1M-BL6C
	☒	8☒	NEMA L5-20P	100-120VAC	20	0	1.9 kVA	16	(16)5-20R	100	P16DF2M-BL1C
	☒	8☒	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	24	(20)C13, (4)C19	200	P24DF3M-BL1C
	☒	8☒	NEMA L5-30P	100-120VAC	30	2	2.9 kVA	24	(24)5-20R	100	P24DF4M-BL1C
	☒	8☒	NEMA L6-20P	200-240VAC	20	0	3.3 kVA	24	(20)C13, (4)C19	200	P24DF5M-BL1C
	☒	8☒	NEMA L5-30P	100-120VAC	30	2	2.9 kVA	24	(24)5-20R	100	P24DG9M-BL1R
	☒	8☒	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	38	(32)C13, (6)C19	200	P38DF9M-BL1C
	☒	8☒	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	38	(32)C13, (6)C19	200	P38DH0M-BL1R
	200-240VAC		0	IEC 60309 3P+E 9h 60A (IP44)	200-240VAC	60	6	17.3 kVA	24	(12)C13, (12)C19	200
☒		8	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	6	(6)C19	200	P06DE6M-BL6C
☒		8☒	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	24	(18)C13, (6)C19	200	P24DF6M-BL1C
☒		8☒	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	36	(30)C13, (6)C19	200	P36DF8M-BL1C
346-415VAC	☒	1	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	6	(6)C19	240	P06D38M
	☒	8	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	6	(6)C19	240	P06D39M
	☒	8☒	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	24	(12)C13, (12)C19	240	P24D43M
	☒	8☒	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	30	(24)C13, (6)C19	240	P30D05M
	☒	8☒	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	42	(30)C13, (12)C19	240	P42D04M
	☒	8☒	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	42	(36)C13, (6)C19	240	P42D42M
	☒	8	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	6	(6)C19	240	P06D02M
	☒	8☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(12)C13, (12)C19	240	P24D04M
	☒	8☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(24)C13, (12)C19	240	P36D02M
	☒	8☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(48)C13	240	P48D03M
☒	8☒	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	42	(36)C13, (6)C19	240	P42D07M	

: 7☒ : 30 ☒ ☒)☒ : 45 ☒ : /&☒

SmartZone™ G5 ベーシック PDU & インテリジェント PDU

Monitored Per Outlet (MPO)

	Region	Form Factor	Input Plug Type	Input Voltage Range	Input Current per Phase	Circuit Breakers	Apparent Power (kVA)	Outlet Count	Outlet Type	Output Voltage	Panduit Part Number
200VAC, 1-Phase	JPN	OU FULL	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	24	(20)C13, (4)C19	200	P24FC0M-BL1C
	JPN	OU FULL	NEMA L6-30P	200-240VAC	30	2	5.0 kVA	36	(30)C13, (6)C19	200	P36FC3M-BL1C
200-240VAC, 3-Phase	JPN	OU FULL	IEC 60309 3P+E 9h 60A (IP44)	200-240VAC	60	6	17.3 kVA	24	(12)C13, (12)C19	200	P24F05M
	JPN	OU FULL	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	24	(18)C13, (6)C19	200	P24FC1M-BL1C
	JPN	OU FULL	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	36	(30)C13, (6)C19	200	P36FC5M-BL1C
	JPN	OU FULL	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	36	(30)C13, (6)C19	200	P36FC9M-BL1B
	JPN	OU FULL	NEMA L15-30P	200-240VAC, DELTA	30	3	8.6 kVA	36	(30)C13, (6)C19	200	P36FC9M-YL1B
415VAC, 3-Phase	JPN	OU FULL	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	24	(12)C13, (12)C19	240	P24F08M
	JPN	OU FULL	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	36	(30)C13, (6)C19	240	P36F12M
	JPN	OU FULL - Wide	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	36	(24)C13, (12)C19	240	P36F13M
	JPN	OU FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(12)C13, (12)C19	240	P24F10M
	JPN	OU FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(18)C13, (6)C19	240	P24F16M
	JPN	OU FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(24)C13	240	P24F17M
	JPN	OU FULL - Wide	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(24)C13, (12)C19	240	P36F02M
	JPN	OU FULL - Wide	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(30)C13, (6)C19	240	P36F06M
	JPN	OU FULL - Wide +	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(48)C13	240	P48F04M
	JPN	OU FULL - Wide +	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(42)C13, (6)C19	240	P48F06M

Note: Minimum Order Quantity: 30 Pieces Per Part Number, Lead Time: 45 Business Days, Terms: Non-Cancellable/Non-Returnable

Monitored Switched (MS Series)

	Region	Form Factor	Input Plug Type	Input Voltage Range	Input Current per Phase	Circuit Breakers	Apparent Power (kVA)	Outlet Count	Outlet Type	Output Voltage	Panduit Part Number
200-240VAC, 3-Phase	JPN	OU FULL	IEC 60309 3P+E 9h 60A (IP44)	200-240VAC	60	6	17.3 kVA	24	(12)C13, (12)C19	200	P24E32M
415VAC, 3-Phase	JPN	OU FULL	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	24	(18)C13, (6)C19	240	P24E02M
	JPN	OU FULL	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	24	(12)C13, (12)C19	240	P24E03M
	JPN	OU FULL	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	36	(30)C13, (6)C19	240	P36E08M
	JPN	OU FULL - Wide	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	36	(24)C13, (12)C19	240	P36E09M
	JPN	OU FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(12)C13, (12)C19	240	P24E06M
	JPN	OU FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(18)C13, (6)C19	240	P24E12M
	JPN	OU FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(24)C13	240	P24E13M
	JPN	OU FULL - Wide	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(24)C13, (12)C19	240	P36E02M
	JPN	OU FULL - Wide	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(30)C13, (6)C19	240	P36E06M
	JPN	OU FULL - Wide +	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(48)C13	240	P48E04M
JPN	OU FULL - Wide +	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(42)C13, (6)C19	240	P48E06M	

Note: Minimum Order Quantity: 30 Pieces Per Part Number, Lead Time: 45 Business Days, Terms: Non-Cancellable/Non-Returnable

SmartZone™ G5 ベーシック PDU & インテリジェント PDU

Monitored & Switched Per Outlet (MSP0)

	Region	Form Factor	Input Plug Type	Input Voltage Range	Input Current per Phase	Circuit Breakers	Apparent Power (kVA)	Outlet Count	Outlet Type	Output Voltage	Panduit Part Number
200-240VAC, 3-Phase	JPN	0U FULL	IEC 60309 3P+E 9h 60A (IP44)	200-240VAC	60	6	17.3 kVA	24	(12)C13, (12)C19	200	P24G05M
415VAC, 3-Phase	JPN	0U FULL	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	24	(18)C13, (6)C19	240	P24G07M
	JPN	0U FULL	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	24	(12)C13, (12)C19	240	P24G08M
	JPN	0U FULL	IEC 60309 3P+N+E 6h 16A (IP44)	346-415VAC	16	0	11.0 kVA	36	(30)C13, (6)C19	240	P36G15M
	JPN	0U FULL - Wide	IEC 60309 3P+N+E 6h 32A (IP44)	346-415VAC	32	6	22.0 kVA	36	(24)C13, (12)C19	240	P36G16M
	JPN	0U FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(12)C13, (12)C19	240	P24G10M
	JPN	0U FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(18)C13, (6)C19	240	P24G18M
	JPN	0U FULL	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	24	(24)C13	240	P24G19M
	JPN	0U FULL - Wide	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(24)C13, (12)C19	240	P36G02M
	JPN	0U FULL - Wide	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	36	(30)C13, (6)C19	240	P36G06M
	JPN	0U FULL - Wide +	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(48)C13	240	P48G04M
	JPN	0U FULL - Wide +	NEMA L22-30P	346-415VAC	30	6	17.3 kVA	48	(42)C13, (6)C19	240	P48G06M

Note: Minimum Order Quantity: 30 Pieces Per Part Number, Lead Time: 45 Business Days, Terms: Non-Cancellable/Non-Returnable

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300



©2022 Panduit Corp.
ALL RIGHTS RESERVED.
PUSP83--WW-ENG
3/2022